

# Grano Dust

## Technical Data Sheet



### PACK SIZE

Available in Maxipack and Bulk bags

### DESCRIPTION

4mm granitic material conforming to the requirements of BS EN 12620.

### USES

When mixed with sand and cement produces a mortar ideally suited for floor screeds, monolithic and granolithic.

### SUGGESTED MIX DESIGN

The below are only suggested mix designs. The user should carry out trials and adapt designs to their own needs.

|                  | Heavy Duty 12mm Depth | Heavy Duty 20-34mm Depth |
|------------------|-----------------------|--------------------------|
| Cement           | 50kg                  | 50kg                     |
| Dried Sharp Sand | 88kg                  | -                        |
| 3mm Sand         | -                     | 150kg                    |
| Grano Dust       | 88kg                  | 50kg                     |



### RECOMMENDATIONS

Do not use when the air temperature is below 2°C or when the ground is frozen.

Wet mortar should be protected from drying out too rapidly. Cover placed material with plastic sheet or wet hessian.

Allow mortar to dry sufficiently (time dependent on ambient conditions) prior to proceeding with further work.

### TECHNICAL SUPPORT

For further advice please contact Hanson Cement's Technical Helpline on 0330 123 2441.

### HEALTH AND SAFETY

Please refer to Material Safety Data Sheet for full information.

#### For further information contact:

Hanson Cement  
Ketton  
Stamford  
Lincolnshire  
PE9 3SX

#### Customer Services:

Tel: 0330 123 4525  
Email: [cement@hanson.com](mailto:cement@hanson.com)

[Hanson-packedproducts.co.uk](http://Hanson-packedproducts.co.uk)

